

Ready for heavy work



FLAIL MOWER KMZ/KMV



Herder takes mowing to new heights

Herder has a name to maintain in Landscape Management. Considering all their innovations, the company from Middelburg has done more than press beyond the limits in the manufacture of flail mowers and other equipment. Sustainable materials and a well-thought out approach guarantee quality performance for a long time. With Herder's boom flail mowers, you'll be assured of a long performance life under all conditions and in all circumstances.



A boom flail mower for Landscape Maintenance

Mowing road shoulders, ditch banks and water channels? You can do that easily with Herder boom flail mowers. With the addition of a lifting function, you can now mow effortlessly on all waterway banks and in shallow ditches without causing damage to the bottom ground or the waters. There are even more reasons to choose a Herder mower.



Do more in one single movement

You will get more out of one single movement, because the machine is provided with a lateral vegetation waste outlet, as well as a suction ventilator. The safety screen is easily changed to allow mounting of a conveyer belt or a bucket. The flail mowers are available in different widths. Available with three different cutting width: 180, 225 and 275 centimetre models. Which cutting width works best for you is determined by the working capacities of your tractor, and working conditions. Moreover, this flail mower benefits from a combination with a KMV standard flail mower for double the width in one run.



Herder takes mowing to new heights

Ergonomic and sustainable quality of work, the highest yield in one run, and realisation of the best results in the process of landscape care. Herder proves with its flail mowers that it can be done. Should you wish to experience mowing on a higher level, don't hesitate to obtain free information from us. Ask your dealer or search on herder.nl for retail outlets.

Robust and exceptionally reliable

Herder Flail mowers are robust and exceptionally reliable. The machines are built for heavy work under extreme circumstances, and can be used for work on road shoulders, rough ground and ditch bank roads. Flail mowers work best in combination with Herder Grenadier, Herder Cavalier or Herder Musketier, and other machines with large capacities.



Get more out of it in one run

The standard flail mowers are suitable for use in combination with a mechanically driven side or arm flail mower. Moreover, this machine includes an option to mount a conveyor belt or a bucket instead of a safety screen. Lateral vegetation drain and the use of a vacuum ventilator for disposal become possible in one movement. Standard flail mowers are available in 225, 275 and 300 centrimetre cutting widths models.



A Sideshift can be extended up to 70 cm.

Ergonomic and safe way of working

Ergonomics and safety at work have always been the leading concern at Herder. You can count on a machine that is user friendly and easy to maintain. A 75 cm Sideshift diminishes the need for unnecessary manoeuvring, and that increases the amount of satisfaction you get from work in return. Safety factor is guaranteed by use of high-quality materials and a balanced construction. A transport lock is integrated as a functionality.



The best standard flail mower

More and more people put their trust into the ultimate quality of Herder products. Machines with the best price/quality ratio, built for one long and sustainable life cycle. There is one more important reason why you should choose a Herder machine - it is the maturity of the manufacturing facilities, that for over 80 years have enjoyed the leading position in the market.



TECHNICAL SPECIFICATIONS KMZ - STANDARD MODEL

Technical specifications

Flails Flail 40 x 12 or Flail 1,2 kg

Impact protection in front as well as behind

Sideshift 60cm

Operation Tractor Hydraulics

Source of Energy

The tractor has to be provided with 2x double action function and 1x single action function

Required nominal capacity 60kW (depending on the cutting width)

Measurements	KMZ180	KMZ225	KMZ275
--------------	--------	--------	--------

Transport width	around 1955 mm*	around 1955 mm*	around 1955 mm*
------------------------	-----------------	-----------------	-----------------

Weight	1505 kg	1590 kg	1675 kg
---------------	---------	---------	---------

Optional

Rear side Standard rubber protection, can be replaced by a heavy-duty transport belt.

Controls Electric/Hydraulic controls featuring a joystick for a 1x single-acting tractor function (with or without Load Sensing)

PTO Rotation speed 1000 rpm

* Attention: it is not centered in the middle of the tractor, and has wider margins on the right.

TECHNICAL SPECIFICATIONS KMV - STANDARD MODEL

Technical specifications

Flails Flail 40 x 12 and Flail 1,2 kg

Sideshift 70cm

Source of Energy

The tractor has to be provided with 1x double-action function

Required nominal capacity 60kW (depending on the cutting width)

Measurements	KMV225	KMV275	KMV300
--------------	--------	--------	--------

Transport width	around 2520 mm	around 3000 mm	around 3240 mm
------------------------	----------------	----------------	----------------

Weight	1015 kg	1095 kg	1135 kg
---------------	---------	---------	---------

Optional

Rear side Standard rubber protection, can be replaced by a heavy-duty transport belt.

Suspension Reversible three-point hitch (sideshift 70 cm) or front mounted deck (sideshift 60 cm).

PTO Rotation speed 1000 rpm



You will achieve more with Herder



Flail mower-ENG-02

www.herder.nl